

Standard Balls and with EPDM topping



Data sheet No. 9353- R - 09 Edition: January 2024

1. Applications

EUROFLEX® Balls are used as seating and communication islands in playing areas and also as playing components.

EUROFLEX® Balls are manufactured by an environment-friendly process and can be recycled das process raw material at the end of their service life.

2. Material

Rubber granulate: granulated recycled rubber

Binding agent: MDI polyurethane

3. Characteristics

Colour: red, green, grey or black

(minor colour variation possible)

Surface: smooth with open pores

4. Dimensions / Tolerances

Diameter: approx. 345 mm, 500 mm, 695 mm
Weight: approx. 18,3 kg, 56,0 kg, 150,4 kg

Tolerances: +/- 0,8%

Dimension steel anchors: Ø 42,8 mm, length approx. 750 mm

5. Material Ball with EPDM topping

Rubber granulate: granulated recycled rubber

Binding agent: MDI polyurethane

Topping: Coloured EPDM rubber granulate





All information without guarantee, subject to change. The Data Sheet is not subject to any change service. Each current and valid from can be recalled at www.kraiburg-relastec.com/euroflex











Standard Balls and with EPDM topping



Data sheet No. 9353- R - 09 Edition: January 2024

6. Characteristics

minor colour variation possible

Surface: smooth with open pores

7. Dimensions / Tolerances

Diameter: approx. 345, 500, 695 mm

Weight: approx. 20,4 kg, 60,0 kg, 166,0 kg

Tolerances: +/- 0,8 %

Dimension steel anchors: Ø 42,8 mm, length approx. 750 mm

8. Test Data

Conformity acc. to Regulation (EC) 1907/2006 SVHC list and appendix XVII

Production facility inspection

9. Installation

Install EUROFLEX® Ball by inserting their steel anchors.

All information without guarantee, subject to change. The Data Sheet is not subject to any change service. Each current and valid from can be recalled at www.kraiburg-relastec.com/euroflex





