

**1. Application**

EUROFLEX® Riding-Toy slabs minimize depression formation around the toy, avoiding puddles and facilitating care and maintenance.

Soft and resilient slabs provide optimum impact protection around spring mounted riding toys.

Integrated connector pins make installation easy and cost efficient.

EUROFLEX® Riding-Toy slabs are manufactured by an environment-friendly process and can be recycled as process raw material at the end of their service life.

They can be played on under almost any weather conditions.

**2. Material**

Rubber granulate: recycled rubber granulate

Binding agent: MDI polyurethane

**3. Product design**

Colour: red, green, black or grey  
minor colour variations and/or fading possible

Surface: smooth with open pores

Other data: plastic connector pins included

**4. Dimension/Tolerance**

Length x Width x Thickness: 1300 x 900 x 50 mm (two-piece) for spring diameter  
max. 250mm

Weight: approx. 16,5 kg/ half part, approx. 33kg complete bordering



Dimensional tolerances: length, width: +/- 0,8 %, thickness: +/- 2 mm

### 5. Test data

Conformity acc. to Regulation (EC) 1907/2006 SVHC list and appendix XVII  
Production facility inspection

### 6. Installation

The Riding-Toy slab could be installed on unbounded subbase or glued on concrete or asphalt.

Note complete installation instruction.