



### 1. Application

EUROFLEX<sup>®</sup> Soft Grip tiles combine extremely high slip-resistant properties with pleasant walking comfort and are especially suitable for high-traffic areas such as walkways, sloping surfaces, overpasses and barrier-free areas.

### 2. Material

Rubber granulate: Substructure: rubber recycled granulate  
Top layer: PES/glass yarn fabric on both sides with special PVC paste, surface sprinkled with PVC granulate.

Binder: MDI Polyurethan

### 3. Design

Colour: Substructure: black  
Top layer:

### Order quantity from 10m<sup>2</sup> for beige and brown



Salt & Pepper Anthracite Brown Red Terra Beige Green Blue

### The other colors from 50m<sup>2</sup> order quantity.

Surface: open porous smooth  
Bottom side: dimple textured  
edges: bottom  
Other: connector pins included

### 4. Dimension/ Tolerances

Length x width x thickness: 1000 x 1000 x 30mm  
Weight: approx. 25kg  
Tolerances: Length, width: +/- 0,8%, thickness: +/- 2mm

### 5. Test data

Production facility inspection  
Slip resistance: R 12 DIN 51130:2014-02  
Fire resistance: Bfl s2 DIN EN 13501-1:2018

### 6. Installation

The substrate must be frost-proof and level. The slabs can be laid directly on a bonded or unbonded substructure.

The slabs can be laid both in a T-joint and in a cross-joint.

For further information, please refer to the installation instructions.

All information without guarantee, subject to change. The Data Sheet is not subject to any change service.  
Each current and valid from can be recalled at [www.kraiburg-relastec.com/euroflex](http://www.kraiburg-relastec.com/euroflex)