





supercell DC 2

Product data sheet no. 9171 - R - 05

Issue: March 2023

SPORTEC® **supercell DC 2** is a versatile, extremely lightweight foam mat that can be used over its entire surface or as a shock pad for a wide variety of applications. The product is supplied in 2x1 m format and can easily be cut to size.


Material

Material:

A mixture of recycled PU-foam and Latex granules bonded with polyurethane elastomer

Product design

Colour(s):



supercell DC2

Surface: granule structure

Note: low colour differences are conditional of material

Dimensions / Tolerances / Weight

Thickness(es): 10 and 20 mm (-5 / +15%)

Length x width: $2000 \text{ mm x } 1000 \text{ mm } (\pm 10 \text{ mm})$

Density: approx. 180 kg/m³

Area weight: 1.8 kg/m² at 10 mm

3.6 kg/m² at 20 mm

The product data sheet is not subject to any change service! All information is without guarantee. Latest version of this document available on www.kraiburg-relastec.com/sportec



page 1 of 2

















supercell DC 2

Product data sheet no. 9171 - R - 05

Issue: March 2023

Product Testing

Tensile strength: min. 0,1 N/mm² (EN ISO 1798)

Elongation at break: min. 55% (EN ISO 1798)

Force reduction: 35% (at 10 mm) (internal tested)

54% (at 20 mm) (internal tested)

Stress -dynamic: 15 mm = 0.019 N/mm² (at 10% compression; internal

tested)

15 mm = 0.033 N/mm² (at 20% compression; internal

tested)

15 mm = 0.046 N/mm^2 (at 30% compression; internal

tested)

 $30 \text{ mm} = 0.029 \text{ N/mm}^2$ (at 10% compression; internal

tested)

 $30 \text{ mm} = 0.047 \text{ N/mm}^2$ (at 20% compression; internal

tested)

30 mm = 0.067 N/mm² (at 30% compresison; internal

tested)

VOC emission rating:



Installation

Installation has to be done in accordance to the Installation Recommendation of **SPORTEC® supercell DC 2**. The latest version of the Installation Recommendation can be downloaded at the website of KRAIBURG Relastec GmbH & Co. KG.

The product data sheet is not subject to any change service! All information is without guarantee. Latest version of this document available on www.kraiburg-relastec.com/sportec





