

KRAITEC® top FiRe
special equipped structural protection mats

| Item | Quantity | Description | Unit Price [Euro] | Price [Euro] |
|------|----------|--|-------------------|--------------|
| | | <p>KRAITEC® top FiRe is a special equipped structural protection mat for high-quality waterproofing systems and insulation systems which provides physical protection in compliance with DIN 18531, 18533 and 18535.</p> <p>KRAITEC® top FiRe has flame-retardant equipping which contributes to a significant reduction in the fire load on flat roofs.</p> <p>KRAITEC® top FiRe is a Broof (t1) classified building protection mat, which is considered a “hard roofing” that is resistant to flying sparks and radiant heat.</p> <p>These structural protection mats fabricated from granulated rubber crumbs have a density of approx. 810 kg/m² and an B_{fi} S1 fire resistance rating (hardly fire resistance) according to EN 13501 Part 1. They are available in thicknesses 8 mm</p> <p>Installation to be carried out as specified in manufacturer’s installation instructions.</p> <p>Manufacturer: KRAIBURG Relastec GmbH & Co. KG Fuchsbergerstr. 4, D-29410 Salzwedel / Germany Tel.: +49/8683-701-167 Fax: +49/8683-701-4177</p> | | |

This data sheet is not subject to change management! No liability accepted for errors or omissions.
The current valid version can be called up at www.kraiburg-relastec.com/kraitec

KRAITEC® top FiRe
special equipped structural protection mats

| Item | Quantity | Description | Unit Price [Euro] | Price [Euro] |
|------|----------|--|-------------------|--------------|
| 1. | _____ | m ² KRAITEC® top FiRe structural protection mats, length l = 2000 / 2300 mm, width w = 1000 / 1150 mm, thickness 8 mm. To be supplied, unloaded from transport lorry and brought to the point of installation. | | |
| 1.1 | _____ | alternative: m ² KRAITEC® top FiRe roll-form structural protection mats, length l = _____ mm, width w = 1250 mm, thickness 8mm. To be supplied, unloaded from transport lorry and brought to the point of installation. | | |
| 2. | _____ | m ² installation of mats in loose masonry-style configuration, with min. 5 cm width overlap and min. 10 cm length overlap. (Installation to be carried out as specified in manufacturer's installation instructions.) | | |
| 3. | _____ | alternative: m ² separating layer (required material and thickness to be specified/approved by roofing membrane manufacturer) to be supplied and installed. Materials: _____ Labour: _____ | | |

DISCLAIMER:

With our information we desire to advise you to the best of our knowledge and belief based on our trials and experiences. However, KRAIBURG Relastec GmbH & Co. KG cannot accept a warranty for the processing result in the specific case, due to the variety of use possibilities, and the storage, processing, and construction site conditions for our KRAITEC® products that are beyond our control. The customer must execute his own tests. Our technical customer service organization is available to you.

This data sheet is not subject to change management! No liability accepted for errors or omissions.
The current valid version can be called up at www.kraiburg-relastec.com/kraitec