

KRAITEC® top plus
Fleece-laminated structural protection mat

Call for application text No. 9205a. - R - 02
Version: January 2018

Item	Quantity	Object	Unit price [Euro]	Amount [Euro]
		<p>KRAITEC® top plus is a fleece-laminated protective layer / layer in the sense of DIN 18531, 18533, 18535 as well as the national (German) flat roof guidelines this is used to protect against mechanical damage on the flat roof.</p> <p>In accordance with EN 12691 (resistant to impact load) the maximum drop height starting at 6 mm thickness is ≥ 2500 mm. In accordance with SIA 280 (mechanical disruptive strength) the max. drop height at 6 mm thickness is 800 mm. (8 mm thickness: max. 1000 mm; 10 mm thickness: max. 1300 mm).</p> <p>The fleece-laminated structural protection mat of rubber granulates, volume weight approx. 810kg/m^3, normally flammable (E_{fl}) in accordance with EN 13501 Part 1, is available in thicknesses from 6 mm to max. 12 mm.</p> <p>Processing in accordance with the installation instructions provided by the manufacturer.</p> <p>Manufacturer: KRAIBURG Relastec GmbH & Co.KG Fuchsbergerstr. 4 29410 Salzwedel, Germany Tel. +49/8683-701 167 Fax +49/8683-701 4167</p>		

This data sheet is not subject to change management! No liability accepted for errors or omissions.
The current valid version can be called up at www.kraiburg-relastec.de/kraitec

KRAITEC® top plus
Fleece-laminated structural protection mat

Call for application text No. 9205a. - R - 02
Version: January 2018

Item	Quantity	Object	Unit price [Euro]	Amount [Euro]
1.	_____	m ² KRAITEC® top plus structural protection rolls of rubber granulate Length = _____mm, width = 1250 mm, thickness d = ___mm deliver, unload from truck and transport to the place of use.		
1.1.	_____	m ² KRAITEC® top plus rolls must be installed loose, offset with at least 5 cm longitudinal seam and 10 cm transverse seam (head butt) overlap in the bond. (The installation instructions must be complied with.) Material: _____ Wages: _____		

DISCLAIMER:

With our information we desire to advise you to the best of our knowledge and belief based on our tests and experiences. However, KRAIBURG Relastec GmbH & Co. KG cannot accept a warranty for the processing result in the specific case, due to the variety of use possibilities, and the storage, processing, and construction site conditions for our KRAITEC® products that are beyond our control. The customer must execute his own tests. Our technical customer service organization is available to you.

This data sheet is not subject to change management! No liability accepted for errors or omissions.
The current valid version can be called up at www.kraiburg-relastec.de/kraitec